



Electronic Crane Scales



Crane Scale (Foundry)

MODEL	Capacity (t)	1	2	3	5	10	15	20	30	50
CS-01 FS	Accuracy (kg)	0.5	0.5	1	1	2	5	5	10	10

Technical Specification:

- Display : LCD With Back light
- Zero Range : 4% FS
- Tare Range 20% FS
- Stable Time : Less than 10 seconds
- Max Safety Overload : 125% FS
- Ultimate Load : 400% FS
- Battery Life : \geq 50 Hours
- Scale Battery : 6 V 4 Ah Ni-H Battery
- Indicator Battery type : 7.2 V/ 2.8 Ah
- Operating Temperature : 1800 Deg.C
- Operating Humidity : \leq 85 Rh under 20
- Operation Distance : 200 mtr wide space
- Frequency : 450 Mhz

Unique Features:

- Stainless steel housing
- High tension shackle and hook
- Data save in case of power failure
- Turn-off automatically after 1 hour with no-operation
- Data records of 2000 weighing
- Keyboard calibration

Optional :

- RS-232 C
- Extra LED Display

Crane Scale (Standard)

MODEL	Capacity (t)	1	2	3	5	10	15
CS-01	Accuracy	0.5	0.5	1	1	2	5

Technical Specification:

- Display : LED Display 25 mm height
- Zero Range : 4% FS
- Tare Range 20% FS
- Stable Time : Less than 10 seconds
- Max Safety Overload : 125% FS
- Ultimate Load : 200% FS
- Battery Life : \geq 12 Hours
- Scale Battery : 6 V 4 Ah Ni-H Battery
- Operating Humidity : \leq 85 Rh under 20

Unique Features:

- Cast Alluminum housing
- High tension shackle and hook
- Power Save Mode
- Keyboard calibration
- Remote tare & power off

Optional :

- Wireless Indicator
- Printer



Counting function



Large pan size



Large LED display



Optional display



Built-in battery charger



Overload protection



External software calibration



Multiple weighing units



Transport protection

Crane Scale (Heavy duty)



MODEL	Capacity (t)	20	30	50
CS-01 HD	Accuracy (kg)	5	10	10

Technical Specification:

- Display : LED Display 25 mm height
- Zero Range : 4% FS
- Tare Range 20% FS
- Stable Time : Less than 10 seconds
- Max Safety Overload : 125% FS
- Ultimate Load : 200% FS
- Battery Life : \geq 12 Hours
- Scale Battery : 6 V 4 Ah Ni-H Battery
- Operating Humidity : \leq 85 Rh under 20

Unique Features:

- Cast Alluminum housing scale body
- High tension shackle and hook
- Power Save Mode
- Keyboard calibration

Optional :

- Wireless Indicator
- Printer

Hanging Scale

MODEL	Capacity (Kg)	30	60	100	150	200	300
CS-01 HS	Accuracy (g)	5	10	10	20	20/50	100

Technical Specification:

- Display : 7 Segment, Six Digit with decimal points
- Power source : 230 V AC, 50 Hz
- Power Consumption : 10 Watts approx.
- Operating temperature : upto 60 Deg. C
- Operating Humidity : 95% RH Max (Non condensing)

Unique Features:

- High internal resolution
 - High Precision loadcells
 - Fast weighing response
 - High bright RED/GREEN LED display
 - Transport and overload protection
 - Software Calibration
 - Economical and affordable price
 - Available in SS-304 Housing Also
- Optional : Bluetooth connectivity



All Sansui models meet the statutory & regulatory requirements as per the provisions of standards of legal metrology act 2009 & legal metrology enforcement rule, 2011.

- Meets or exceeds OIML standards
- All the dimensions are mentioned in mm
- Due to continuous R & D efforts all the specifications are subject to change without any prior notice.
- The catalog represents our standard specifications. But it is our pleasure to attend any special requirements of buyer.

*Customised weighing scales are available on demand. Like fully SS body, Printer option, Wireless option RF / Wi-Fi & different structure sizes for platform etc.



ISO 9001:2008

SANSUI ELECTRONICS PVT. LTD.



E-59, Marketyard, Gultekdi, Pune - 411 037 Maharashtra, India

Mobile : 98238 88888 / 88066 66092
Support : 97644 51000 / 97644 91000

sales@sansui.co.in
sansuiscales.com

- Pune • Mumbai • Navi Mumbai • Kolhapur • Nashik • Delhi • Parwanoo • Kolkata • Bhubaneswar • Indore • Ludhiana • Bhopal • Hyderabad • Bengaluru • Chennai •